



## SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0

### **DESCRIPTION:**

**SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0** is multipurpose premium quality lithium grease specially designed with high quality mineral oil and advance performance additives for industrial applications where extreme pressure and water washout property required.

### **APPLICATION:**

**SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0** is Suitable for a wide range of industrial uses such as plain and anti-friction bearings in steel mills, paper mills, press machine and generator, pumps, conveyors, compressors, machine tools, gears and various types of couplings.

### **SPECIFICATIONS:**

**SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0** meets the following performance specification requirement:

- NLGI # 2
- NLGI # 0

### **ADVANTAGES:**

**SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0** offers the following advantages:

- Excellent in high load-carrying abilities.
- Superior at oxidation stability.
- Superior at lubricity.
- Excellent in thermal resistance.
- Excellent in low temperature characteristics.
- Superior at water resistance.
- Good for rust preventive ability.



## SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0

### **TECHNICAL SPECIFICATIONS:** SAVSOL GREASE XHD-2 & SAVSOL GREASE XHD-0

CHARACTERISTICS	ASTM METHOD	SAVSOL GREASE XHD-2	SAVSOL GREASE XHD-0
Appearance	Visual	Blackish Brown, Smooth	Blackish Brown, Smooth
NLGI #	--	2	0
Worked Penetration @ 25 <sup>o</sup> C	D217	265 - 295	355 - 385
Dropping Point <sup>o</sup> C, min	D566	180	180
Copper Strip Corrosion (100 <sup>o</sup> C X 24 hrs)	D130	1	1
Timken Test (OK load), lbs	D2509	45	45

*The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.*

### **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

### **ENVORNMENT, HEALTH AND SAFTEY**

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 27<sup>th</sup> Mar:2019



Savita Oil Technologies Ltd  
66/67, Nariman Bhavan, Nariman Point, Mumbai 400 021, India.  
T: +91 22 2288 3061 / 64 F: +91 22 2202 9364  
W: www.savsol.com E: customersupport@savita.com