



SAVSOL ROCK DRILL OIL

(Rock Drill, Way & Pneumatic Tool Lubricant)

DESCRIPTION:

SAVSOL ROCK DRILL OIL is formulated with high quality paraffinic base oils and premium additive system to provide superior performance in air-powered equipment. It is designed to give maximum protection from component wear in severe service conditions.

It provides a tenacious film of lubrication on cylinder walls and other lubricated components. It has good metal-wetting characteristics, ensuring that the lubricant reaches critical parts rapidly.

APPLICATION:

SAVSOL ROCK DRILL OIL is designed to enhance the operation of percussion type rock drills and associated equipments such as jackhammers, paving breakers, quarry drills, spike drivers, clink breakers and concrete vibrators. Additionally, it is recommended for pneumatic tools such as impact wrenches, rivet hammers, drills and reamers, wood borers, safety saws, diggers, tampers, concrete surfacers, sanders and air hoists as well as cleaning, scaling, caulking and chipping tools.

SPECIFICATION:

SAVSOL ROCK DRILL OIL meets the requirements of all major manufacturers.

ADVANTAGES:

SAVSOL ROCK DRILL OIL offer the following advantages:

- Possess good metal-wetting characteristics ensuring that the lubricant reaches critical parts rapidly.
- Minimizes deposit formations.
- Non-hazardous and non-toxic.
- Excellent resistance to rust & corrosion.
- No disagreeable odour making it ideal for underground operations.

SAVSOL ROCK DRILL OIL

(Rock Drill, Way & Pneumatic Tool Lubricant)

TECHNICAL SPECIFICATIONS: : SAVSOL ROCK DRILL OIL

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
ASTM Colour	D1500	L3.5
Density @ 29.5°C, gm/cm ³	D1298	0.8875
Kin. Viscosity @ 40°C, cSt	D445	105.9
Kin. Viscosity @ 100°C, cSt	D445	11.54
Viscosity Index	D2270	96
Flash Point, COC, °C	D92	226
Pour Point, °C	D97	-6

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

Storage:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

Environment, Health and Safety:

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 04th Sept. 2019